

REI 120 protection for false ceiling recess lights

AF COVER LIGHT is a protection item which allows the insertion of spotlights/ceiling lights on REI false ceilings other than membrane false ceilings. This allows fire resistance that would otherwise be compromised. It is easy to remove and reinstall and no maintenance is required.

AF COVER LIGHT is available in various shapes and sizes depending on the element to be protected. It consists of a glass fabric, the external part is aluminised, the internal part is coated with an intumescent paint. The product is flexible and designed to adapt to all small and medium-sized recessed lights and spotlights.

Easy to remove and reinstall during maintenance. The use of **AF COVER LIGHT** means the design is not based on the fire resistance integrity of the false ceiling on which spotlights have been inserted. The product low weight and flexibility make it easy to install without overloading the false ceiling structure. **AF COVER LIGHT** is much easier to apply than a structure made of mineral fibre sheets.

AVAILABLE SIZES

150X150 mm (conical);
250x250 mm (conical) ;
300x300x250 mm ;
600X600x150 mm;
Other sizes are available upon request.

APPLICATION METHOD:

1. place the **AF COVER LIGHT** flexible protection over the ceiling light (or spotlight) so that the lower edge adheres to the false ceiling extrados;
2. insert the power supply cable between the protection and the false ceiling.

PACKAGING AND STORAGE

On pallet or cardboard boxes.

If the product is stored under standard conditions, there is no storage time limit.

SPECIFICATIONS

Supply and application of **AF COVER LIGHT** firestop flexible protections, made of aluminised glass fibre fabric treated with an intumescent product, providing REI 120 protection of recessed spotlights in fireproof false ceilings.

CERTIFICATIONS

Class REI 120 (UNI EN 1365-2)

Reinforced concrete floor protected by a fibre false ceiling

