

ANTIVANDAL ROLLING SHUTTER RC6



The Safedoor Antivandal Rolling Shutter is a new and innovated product, providing solution against thefts and vandalism.

It is a combination of fireproof and safety rolling shutter.

Suitable for stores, banks, office buildings, etc.

It is certified for RC6 according to EN 1627:2001 and EN 1630:2011.

The fireproof rolling shutter consists of special double closed horizontal galvanized steel profiles, 1,0 mm thickness. These profiles are internally reinforced by steel beams, 2,0 mm thickness up to 2 m total height. Their complex cross-section gives them high stiffness in impact and / or pressure.

The barrel is made of steel pipe, with a diameter of 168 mm and more.

The side guides are made from heavy duty galvanized steel of dimensions 220x120/80.

The operation of the shutter is done electrically with a suitable motor through a push button or manually with a chain.

With optional automation the shutter closes:

- In case of fire
- Glass breakage
- Explosions
- Breaking the relevant sensors or remove them
- Locally increase of temperature up to 68 °C
- By telephone call.

Technical Data

Classification	RC6 / EN 1627:2001 & EN 1630:2011
Installation	Masonry / Metallic construction
Material	Galvanized steel profile
Motor	Single phase or Three phase, side placed
Operation	Auto/ manual
Automation	Optional

Cover box dimensions (for typical dimensions)

Cover	x	y
Motor side	600mm	600mm
Opposite motor side	600mm	600mm

Side guides dimensions

x	y
220 mm	80mm

